



## QINEO GL 302 DC

### TIG DC welding power source up to 290 ampere for manual welding

With their excellent price and performance ratio and their outstanding process functions you can use the QINEO GL-302 TIG Inverter welding power source for a wide range of applications. The welding power source is perfectly suited for on-site applications and repair welding in workshops. The high tolerance to mains voltage fluctuations guarantees best welding results with long cable lengths and when operating on a generator. Equipped as standard for gas-cooled TIG welding torches, the units can optionally be equipped with a cooling module. A trolley and a gas bottle holder are also available for an optimum mobility.

- Excellent price and performance ratio
- Safe arc ignition: Matched start parameters for best ignition conditions
- Suitable for MMA welding: Optimum flow behaviour and more protection due to VoltageReduceControl
- Optimum power and weight ratio The powerful but light partner - everywhere
- Everything at a glance: A clear operating panel for easy handling
- Robust construction: High level of stability of the devices





## QINEO GL 302 DC

### Technical Data

Welding current	5 A - 300 A
Welding current 100% duty cycl	210 A
Open circuit voltage	76 V
Mains voltage	400V / 50Hz / 3 phases
Connection cable	4 x 2,5 mm <sup>2</sup>
Type of protection	IP 23 S
Dimensions (L/W/H) compact uni	460 x 230 x 325 mm
Weight compact unit	19.9 kg

### Application

Manual

### Process

- TIG DC welding

### Questions about the product?

Your contact partner:  
Daniel Weber  
Tel.: +49 (0)2773 85-430  
gt-sales@cloos.de



Technical modifications reserved  
Version: 14.05.2024

**CLOOS**