



## QIROX QRC-230

### **6-axis robot mechanics with classic wrist and 2,300 mm working envelope**

The QIROX QRC-230 is a six-axis articulated arm robot. The robot is used in upright or overhead position and is mounted on a base or directly at a robot positioner. The QIROX QRC-230 robot has a classic wrist where welding torches and other working tools with a weight of up to 12 kg can be mounted.

- Compact solution: Agile and highly dynamic for short cycle times
- Processes: Takes over all MIG/MAG and TIG welding processes, optionally leads a laser sensor
- Flexibility: Modular design for tailor-made systems, perfectly adapted to individual production requirements
- Dynamics: High dynamics due to slim product design, low weight and ergonomic shapes
- Quality: Repeatability, long service life and maintenance intervals





## QIROX QRC-230

### Technical Data

Series

Design

Number of axes

6

Payload

12 kg

Working area

2300 mm

Mounting area

400x400

Robot weight

107 kg

Mounting

Inclination

Processes

TIG Welding (WDF)  
MIG/MAG welding  
MIG/MAG welding (WDD)  
MIG/MAG Tandem welding  
MIG/MAG Tandem welding (WDD)  
TIG welding  
Handling

Attachment parts

### Process

- TIG Welding (WDF)
- MIG/MAG welding
- MIG/MAG welding (WDD)
- MIG/MAG Tandem welding
- MIG/MAG Tandem welding (WDD)
- TIG welding
- Handling

### Questions about the product?

Your contact partner  
Manuel Benner  
Tel.: +49 (0)2773/85-562  
Automation@cloos.de



Technical modifications reserved  
Version: 20.05.2024

CLOOS