

QINEO QuesT-402-DC Premium

TIG DC welding power source up to 400 ampere for automated welding

Start your next TIG mission with QINEO QuesT: The new hightech welding power source solves highly demanding TIG welding tasks reliably and efficiently. The QINEO QuesT is characterised by precise ignition properties and optimal process functions. The stable and focussed arc which is easy to control over the entire power range guarantees excellent welding results. When TIG pulsing, you benefit from the high dynamics of the QINEO QuesT which enables fast current transitions even with large capacity differences - so you get perfect welds. The Deep Pulse function stabilises and focuses the arc so that the arc pressure is increased. This can result in both deep penetration for thick sheets and high speeds for thin sheets. A multitude of components, functions, interfaces and configuration possibilities make the QINEO QuesT Premium to be your individual power source for automated welding - exactly how you need it for your welding tasks. Use the advantages of the CLOOS robot interface (QTI) specially adapted to QINEO QuesT and benefit from the convenient, comprehensive parameter input via the teach pendant of the robot controller, reduced programming times and a perfect welding process. All common industrial interfaces for automation are also available.

- Excellent ignition properties even under difficult conditions
- Excellent control behaviour enables a stable arc over the entire setting range
- · Optimum process functions for best welding results
- Fast transitions even with large capacity differences (TIG pulses)
- Deep-Pulse-Funktion produces a stabilised and focused arc for deep penetration or high welding speeds (Deep Pulse up to 20 kHz)
- Modular design and extensive accessories for individual adjustment of the QINEO QuesT to your needs
- · Digital networking with all common industrial interfaces
- Optimal interface enables access to all setting options of the QINEO QuesT from the robot controller
- Programming via the robot controller accelerates and simplifies the integration of the QINEO QuesT into the program flow
- High-quality components and a robust design in proven CLOOS quality







QINEO QuesT-402-DC Premium

Technical Data			
Construction form	External wire drive		
Welding current	3 A - 400 A		
Welding current 60% duty cycle	350 A		
Welding current 100% duty cycl	400 A		
Open circuit voltage	76 V - 96 V		
Mains voltage	380 V - 480 V / 50 Hz / 3-ph		
Connection cable	4 x 6 mm ²		
Mains protection/400V	32 A		
Type of protection	IP 23		
Insulation class	F		
Type of cooling	F		
Dimensions L/W/H (without wire	700 x 340 x 255 mm		
Weight (without wire drive)	63 kg		

Application
Auto
Process
TIG DC welding

Questions about the product?

Your contact partner:

Daniel Weber

Tel.: +49 (0)2773 85-430 gt-sales@cloos.de



Technical modifications reserved Version: 14.05.2024

