



QINEO StarT 402 Eco

MIG/MAG welding power source up to 400 ampere for manual welding

Simply weld better with the QINEO StarT: The welding power source offers you an easy entry into the world of manual welding. Use the advantages of the three available CLOOS welding processes in addition to the standard processes. This allows you to start welding immediately – without a long parameter search. Benefit from numerous optional components and functions. This makes the QINEO StarT your individual power source - exactly as you need it for your manual welding tasks.

- High-quality components with optimum price/performance ratio and excellent welding characteristics
- Faster to the target with the preset parameters of three CLOOS welding processes
- Choose the wire drive that best suits the welding task
- Simple, quick and intuitive operation with the MasterPlus Compact operating module
- Modular design and extensive accessories for flexible application possibilities adapted to individual requirements





QINEO StarT 402 Eco

Technical Data

Construction form	External wire drive
Welding current	15 A - 400 A
Welding current 100% duty cycl	400 A
Open circuit voltage	78,7 V
Connection cable	4 x 6 mm ²
Mains protection/400V	32 A
Type of protection	IP 23
Insulation class	F
Type of cooling	F
Dimensions L/W/H (without wire	819 x 348 x 498 mm
Weight (without wire drive)	56 kg

Application

Manual

Process

- MIG Brazing
- MIG/MAG singel wire

Questions about the product?

Your contact partner:
Daniel Weber
Tel.: +49 (0)2773 85-430
gt-sales@cloos.de



Technical modifications reserved
Version: 12.05.2024

CLOOS