



QINEO TIG-HF-E-WD-RF-Mono

External TIG ignition module with equipment for the Mono wire drive system

The external ignition module (QINEO TIG-HF-E) that can be combined with QINEO QuestT ensures safe ignition of the TIG arc with long cable distances between the QINEO QuestT and the welding torch. The module is mounted close to the welding process so that the torch cable assembly can be made as short as possible. The short transmission distance of the ignition voltage reduces interference to surrounding components and prevents ignition voltage losses in large overall systems. You can connect up to four ignition modules to a QINEO Quest. This enables the alternating operation of several welding torches and wire drives on one power source. The ignition module has a modular design, numerous standard monitoring components (e.g. water flow sensor, temperature monitoring, ignition voltage monitoring, etc.) and is equipped with a connection for the Mono wire drive system. The ignition module is also available with additional options.

- Safe ignition with long cable lengths between power source and welding torch
- Simple construction of complex installations and systems by using the ignition module with ignition voltage-free cables to the QINEO QuestT
- Increased system availability due to minimised influence of possible interferences of the HF ignition voltage on other system components





QINEO TIG-HF-E-WD-RF-Mono

Technical Data

| | |
|-------------------|--------------------|
| QN_ZU_ABMESSUNGEN | 500 X 253 X 190 mm |
| QN_ZU_GEWICHT | 12 |

Application


Auto

Process

- TIG AC/DC welding
- TIG DC welding

Questions about the product?

Your contact partner:
Daniel Weber
Tel.: +49 (0)2773 85-430
gt-sales@cloos.de



Technical modifications reserved
Version: 16.05.2024

CLOOS